

## Double-Wire Clamps - SAE Type "A"

Double sealing action, plated to protect against rust and corrosion.

Unique Swivel Nut:

- Nut is integral part of clamp to prevent loss.
- Nut remains perfectly aligned with screw.
- Standard zinc plated material; other plating types available.
- Standard wire diameter: 12 gauge (.1055 in +/- .003in) (2.68mm +/- .08mm)

Wire Grips are non-stocking parts. Produce and release policy requires firm purchase order and specific release dates.

Packaging: Bulk.- Minimum Lot sizes apply. - Patent Numbers 2,536,612 , 4,414 ,715 , 4,592,576



### Rated Ultimate Torque:

40in.lbs. min. (4.5Nm)

### Recommended Installation Torque:

20-25in.lbs. (2.3 - 2.8Nm)

| SAE No. | Part Number | Inches |        | Millimeters |        |
|---------|-------------|--------|--------|-------------|--------|
|         |             | Open   | Closed | Open        | Closed |
| 34      | 102100      | 1.06   | 0.94   | 26.9        | 23.9   |
| 36      | 102102      | 1.12   | 0.99   | 28.4        | 25.1   |
| 38      | 102104      | 1.19   | 1.06   | 30.2        | 26.9   |
| 40      | 102106      | 1.25   | 1.12   | 31.8        | 28.4   |
| 42      | 102108      | 1.31   | 1.16   | 33.3        | 29.5   |
| 44      | 102110      | 1.38   | 1.19   | 35.1        | 30.2   |
| 46      | 102112      | 1.44   | 1.25   | 36.6        | 31.8   |
| 48      | 102114      | 1.50   | 1.31   | 38.1        | 33.3   |
| 50      | 102116      | 1.56   | 1.38   | 39.6        | 35.1   |
| 52      | 102118      | 1.62   | 1.44   | 41.1        | 36.6   |
| 54      | 102120      | 1.69   | 1.50   | 42.9        | 38.1   |
| 56      | 102122      | 1.75   | 1.56   | 44.5        | 39.6   |
| 58      | 102124      | 1.81   | 1.62   | 46.0        | 41.1   |
| 60      | 102126      | 1.88   | 1.69   | 47.8        | 42.9   |
| 62      | 102128      | 1.94   | 1.75   | 49.3        | 44.5   |
| 64      | 102130      | 2.00   | 1.81   | 50.8        | 46.0   |
| 66      | 102200      | 2.06   | 1.88   | 52.3        | 47.8   |
| 68      | 102202      | 2.12   | 1.94   | 53.8        | 49.3   |
| 70      | 102204      | 2.19   | 1.97   | 55.6        | 50.0   |
| 72      | 102206      | 2.25   | 2.03   | 57.2        | 51.6   |
| 74      | 102208      | 2.31   | 2.12   | 58.7        | 53.8   |
| 76      | 102210      | 2.38   | 2.19   | 60.5        | 55.6   |
| 78      | 102212      | 2.44   | 2.25   | 62.0        | 57.2   |
| 80      | 102214      | 2.50   | 2.28   | 63.5        | 57.9   |
| 82      | 102216      | 2.56   | 2.34   | 65.0        | 59.4   |
| 84      | 102218      | 2.62   | 2.41   | 66.5        | 61.2   |
| 86      | 102220      | 2.69   | 2.47   | 68.3        | 62.7   |

